VIB 100 CA
CIRCULAR VIBRATOR
VIBRADOR CIRCULAR

VIBRATOR FOR SURFACE FINISH
Circular-vibrating machines used for the deburring, grinding and polishing of metal and plastic items.

VIBRADOR PARA ACABADO SUPERFICIAL
Máquinas vibratorias circulares utilizadas para desbarbar, alisar y pulir piezas de metal y plástico.

CHARACTERISTICS
- Metal tank with anti-abrasive and oil-proof polyurethane coating
- Ascending-type canal: particularly efficient discharge ability
- Integrated and interchangeable metal or PVC separation grid for pieces discharge
- Manual or automatic lifting ramp for pieces discharge
- Fast-unloading lower discharge outlet with integral-polyurethane cap
- Moto-vibrator equipped with adjustable eccentric weights
- Control panel provided with:
  - Timer for retarded start-of-cycle programming
  - Timer for work-cycle duration
  - Button to pieces-discharge starting
  - Timer for discharge-cycle duration
  - Emergency button
  - General switch
- Quick and easy to use
- Collection canal with capillary holes for the washing and rinsing of the finished product
- Faucet for water discharge

Optional
Inverter for RPM / workforce regulation
Soundproofing lid or cover

CARACTERÍSTICAS
- Depósito metálico con revestimiento de poliuretano antiabrasivo y resistente al aceite
- Canal de tipo ascendente: capacidad de descarga particularmente eficiente
- Rejilla de separación integrada e intercambiable de metal o PVC para descarga de piezas
- Rampa de elevación manual o automática para descarga de piezas
- Salida de descarga inferior de descarga rápida con tapa integral de poliuretano
- Moto-vibrador equipado con pesos excéntricos ajustables
- Cuadro de mandos provisto de:
  - Temporizador para programar inicio de ciclo retardado
  - Temporizador para la duración del ciclo de trabajo
  - Pulsador para piezas-arranque de descarga
  - Temporizador para la duración del ciclo de descarga
  - Boton de emergencia
  - Interruptor general
- Rápido y fácil de usar
- Canal de recogida con orificios capilares para el lavado y enjuague de el producto terminado
- Grifo para descarga de agua

Opcional
Inverter para regulación de RPM / trabajo
Tapa o tapa insonorizante

THECNICAL DATA
DATOS TÉCNICOS

100 l
Tank capacity
Capacidad del tanque

280 mm / 11"
Canal width
Ancho del canal

ASCENDING CANAL
CANALE ASCENDENTE

2500 kg / 5511 lbs
Centrifugal force
Fuerza centrífuga

POWER POTENCIA	**2150 W**
VOLTAGE VOLTAJE	**230 / 400 V - THREE-PHASE | TRIFASE**
FREQUENCY FRECUENCIA	**50 / 60 Hz**
DIMENSIONS DIMENSIONES	**1290 x 1120 x 1020h mm / 50,8 x 44,1 x 40,1 h"**
WEIGHT PESO	**570 kg / 1257 lbs**

Bellavista N.42 Bodega N. 6
San Juan Xalpa
09850 IZTAPALAPA
CIUDAD DE MÉXICO

(+52) 5556136477
(+52) 5556136212
(+52) 5556123770

www.nicem.mx
(+52) 5616796342

Nicem México
nicem.mx